

HOW TO CHOOSE



Select the padding level

SMP4BIKE Professional line models are divided in the table on the right based on the padding level, starting from **Carbon** models and models **without padding**, to models with **high padding**.



What's your pant size?

The models most suited to your physical build are marked with the $\$ symbol in the column that matches your pant size.

Based on the previously selected padding level, find one or more models to choose from for the road test*.

All models are UNISEX.



Test the saddle

Visit our website, send us an e-mail or call us to find your nearest **SMP4TEST dealer.** You can test a saddle on your bike without any purchase obligations. A short adjustment period may be required for the new saddle: to guarantee the reliability of the test, you should ride the saddle at least four-five times, making the necessary adjustments.

For further information on assembly and adjustments, see the instructions at: www.sellesmp.com/smp4bike/en/support/assemble-and-adjust-saddle



A SADDLE



			2 What's your pant size?							
			z USA	29	30-31	32-33	34-35	36-37	38-39	9
			USA UK	26-28	30-32	34-36	38-40	42-44	46-48	rs ol
			⊒ USA	24-25	26-29	30-31	32-33	34-35	36-37	2 yea
			WOW UK	6-8	8-10	12-14	14-16	16-18	18-20	(6-1)
1 Padding level	Model	Saddle width (mm)	ŚŃÞ	XS	S	М	L	XL	XXL	JUNIOR (6-12 years old)
CARBON FIBER	FULL CARBON	129		(\$	₽			•	
	FULL CARBON LITE	135				(E	E		
	CARBON	129				(4)		•	•	
	CARBON LITE	135						E		
NO PADDING	CHRONO	124			(\$:	•	E
	COMPOSIT	129			(P		:	•	
	FORMA	137				(
MINIMUM PADDING	EVOLUTION	129				E			•	
	BLASTER NEW!	131			((1)		•	
	DYNAMIC	138				\$	(E		
STANDARD PADDING	STRATOS	131			\$	\$	(•	
	GLIDER	136				((
	DRAKON	138	:			P	(4)	(
	PR0	148						E	(
PADDING HIGH	LITE 209	139				\$				
	AVANT	154	:				(2)	a	a	
	PLUS	159	:							
	LITE JUNIOR	128				• • • • • • • • • • • • • • • • • • •		•		(1)

^{*} Selle SMP studies have allowed the various saddle models to be associated with different pant sizes (parameter that varies according topelvis width with 75% reliability).